

KDAE-S series



Features

- KDAE-S series are designed for reliable dew point $-40^{\circ}\text{C}(\text{Atm})$ with minimizing overheating of heater. Pre filter and after filter is designed in skid type, easier piping work.

How to Order

KDAE - 20 S

① ② ③

① Series

KDAE	Deciccant air dryer with heater
------	---------------------------------

③ Type

S	Skid
---	------

② Size

50, 75, 100, 130, 150, 200, 250, 300, 400, 500, 600, 750, 1550, 3000, 4100

Specifications

Model	Flow Capacity (Nm ³ /hr)	In/Out Connection Rc(PT)	Gel/ Tower (kg)	Heater (kw)	Dimensions (mm)			Weight (kg)
					Width	Length	Height	
KDAE-50S	523	1 1/2"	174	4.5	1,450	1,500	2,380	890
KDAE-75S	627	1 1/2"	223	5.5	1,550	1,500	2,450	985
KDAE-100S	914	2"	300	7.5	1,750	1,700	2,450	1,320
KDAE-130S	998	2"	394	9.5	1,750	1,700	2,600	1,550
KDAE-150S	1,311	2 1/2"	490	12	1,850	1,800	2,600	1,820
KDAE-200S	1,764	2 1/2"	558	15	1,900	1,850	2,800	2,100
KDAE-250S	2,048	3"	750	18.5	2,800	1,600	2,800	2,320
KDAE-300S	2,804	3"	1,052	25	2,800	1,600	2,650	3,200
KDAE-400S	3,517	4"	1,430	32	3,200	2,500	2,950	5,050
KDAE-500S	4,486	4"	1,688	40	3,300	2,550	2,900	5,100
KDAE-600S	5,130	6"	2,448	60	3,400	2,500	3,200	7,300
KDAE-750S	6,930	6"	2,864	70	3,600	2,800	3,900	9,500
KDAE-1550S	2,952	4"	1,388	32	3,200	1,700	2,880	4,900
KDAE-3000S	5,400	6"	2,376	60	3,600	2,500	3,165	7,200
KDAE-4100S	6,600	6"	2,864	70	3,600	2,800	3,900	9,500

- Air Dryer
- Reference Data
- KDHR
- KDHR-W
- KDHT
- KDAH
- KDAE
- KDAE-S
- KDAO
- KDAB
- KDNP
- KDH-C
- KDRC
- KDRT
- KDHAD
- EZ-1
- KDXF
- KDXE